

Tender-text: BG-FILCOTEN spot



GRASPOINTNER
Sustainable innovation.

1. BG-FILCOTEN spot **yard-gully**, made of FILCOTEN HPC (high performance concrete)
incl. silt bucket, odour trap and outlet DN 100 (pipe coupling).

mesh-grate MW 25/12,5 made of galvanised steel, with fiX-lock, car accessible.

Building biology tested and recommended by IBR (Institut für Baubiologie Rosenheim, DE)

Fire-behaviour class: A1 according to EN13501 - non-combustible

100% recyclable with U-A marking

Delivery and installation according to the manufacturer's installation instructions.

LxWxH: 300x300x419 mm

weight: 21,5 kg



2. BG-FILCOTEN spot **yard-gully**, as described in position 1, but
incl. cast iron frame and mesh-grate MW 25/12,5 made of galvanised steel, with fiX-lock, B125 kN.

LxWxH: 300x300x450 mm

weight: 24,8 kg

3. BG-FILCOTEN spot **yard-gully**, as described in position 1, but
incl. cast iron frame and ductile iron grate made of ductile iron EN-GJS, radial-design, with fiX-lock, B125 kN.

LxWxH: 300x300x450 mm

weight: 26,7 kg

4. **Extension-element** for BG-FILCOTEN spot yard-gully
to increase the capacity

LxWxH: 300x300x276 mm

weight: 12,3 kg

5. **Extension-element incl. drilling** Dm 122 mm, for BG-FILCOTEN spot yard-gully
for the inlet e.g. of a roof drainage pipe

LxWxH: 300x300x276 mm

weight: 11,4 kg