

1. **Drainage channel** with comb profile **BG-FILCOTEN** parkline NW 300 H 50 made of **FILCOTEN** HPC (high-performance concrete)  
 load-class A15 – C250 kN type M, according to EN1433 – CE-certified,  
 Channel element with integrated anchoring pockets, channel joint sealable,  
 Slot-width 18 mm, height 50 mm  
 Building biology tested and recommended by IBR (Institut für Baubiologie Rosenheim, DE)  
 Fire-behaviour class: A1 according to EN13501 - non-combustible  
 100% recyclable with U-A marking  
 Delivery and installation according to the manufacturer's installation instructions.



NW/Height:	LxWxH: [mm]	weight: [kg]	Capacity: [l/m]	eco-indicator: [kg]
NW300 H 50:	1000x305x50	25,3	4,5	CO <sub>2</sub> -Eq. 7,0

---

2. **Drainage channel with outlet**, channel-element as described in position 1, but with bottom outlet, connection for DN100 pipe socket

NW/Height:	LxWxH: [mm]	weight: [kg]	Capacity: [l/m]	eco-indicator: [kg]
NW300 H 50:	1000x305x50	25,0	4,5	CO <sub>2</sub> -Eq. 6,9

---

3. **cross-corner-element**, made of **FILCOTEN** HPC to build crossings, T-pieces and 90°-corners

NW300 H 50:	LxWxH: 305x305x50 mm	weight: 7,6 kg
-------------	----------------------	----------------

---

4. **outlet cover**, made of stainless steel 1.4301 for safe covering of the drain opening

NW300 H 50:	LxWxH: 108x24x60 mm	weight: 0,1 kg
-------------	---------------------	----------------

---

5. **front cap** closed, made of stainless steel 1.4301

NW300 H 50:	LxWxH: 1x292x40 mm	weight: 0,1 kg
-------------	--------------------	----------------

---

6. **Installation chair**, Kit incl. screws for positioning the channel, galvanised steel  
 weight: 1,1 kg
- 

7. **Construction-time barrier**, made of galvanised steel

NW300 H 50:	LxWxH: 1000x300x20 mm	weight: 2,8 kg
-------------	-----------------------	----------------

---

8. **Cleaning-rake**, made of stainless steel 1.4301

NW300 H 50:	LxWxH: 96x267x81 mm	weight: 0,5 kg
-------------	---------------------	----------------